

## Primary Standards

# Hydraulic Dead Weight Testers

**Precision  
Bench-top / Table-top Model**

*Ideal for Fine Increments & for Medium Volume Calibration. Ensures – Easy & Controllable Pressure generation for Calibrating Pressure Gauges / Transducers / Transmitters, Transfer Standards, Recorders, Digital Calibrators etc.*

**Screw Pump with built-in Priming Pump**

### Model

#### BMH6600 Series

- Ranges : Upto 700 Bar
- Accuracy :  $\pm 0.025\%$  of Reading
- Single / Dual Piston
- Oil operated
- Engineering Units : Bar / Kg/Cm<sup>2</sup> / PSI
- Adjustable Foot & Spirit Level
- Piston Calibrated thro' "Cross Floating Techniques"
- Calibrated to Standard Gravity (Customer specific Gravity adjustment can also be done optionally)
- Accuracies Traceable to International Standards
- Non-Magnetic Stainless Steel Weight Sets
- Calibration Certificate – for overall Accuracy + PCU (Area) + Weights (Mass) from NABL Accredited Lab – as per ISO/IEC 17025:2005
- DWTCal Calibration Software - optional



Motorized Version  
- Optional

**PRISMA**  
Instruments  
& Gauge Bourdon France



## Specifications

## BMH6600 Series

Ranges	35 / 70 / 100 / 160 / 350 / 600 / 700 Bar
Piston	Single / Dual
Standard Accuracy	±0.025% of Reading
Traceability	International Standards
Weights	Non-Magnetic Stainless Steel
Pressure generation	Thro' Priming Pump & Screw Ram
Standard Corrections	Gravity : 9.80665 m/s <sup>2</sup> * / Temperature : 20°C / Air Density : 1.2 Kg/Cm <sup>2</sup>
Weight (approx.)	Instrument : 19 Kg. ; Weight Sets : 8 to 33 Kg.
No. of Weights	12 to 15
Instrument Dimensions	530 x 325 x 230 mm (L x W x D)
Operating Fluid	Oil
DWTCal Software	Optional

**Table ①**

Model	Accuracy	PCU	Weight Set	Certification	Remarks
BMH6600	±0.025% of Reading	Tungsten Carbide Piston & Matching Hardened Cylinder	Non-Magnetic Stainless Steel	Overall Accuracy + PCU (Area) + Weights (Mass)	Issued by NABL ISO/IEC 17025:2005 Accredited Lab

**Table ②**

Piston Type	Piston Model	Pressure Ranges		
		1 / Bar	2 / Kg/Cm <sup>2</sup>	3 / PSI
Single	SP-35	0.5 to 35	1 to 35	5 to 500
Single	SP-70	0.5 to 70	1 to 70	10 to 1000
Single	SP-100	5 to 100	5 to 100	75 to 1500
Single	SP-160	5 to 160	5 to 160	80 to 2500
Single	SP-350	5 to 350	5 to 350	80 to 5000
Single	SP-600	10 to 600	10 to 600	160 to 9000
Single	SP-700	10 to 700	10 to 700	150 to 10000
Dual	DP-160	1 to 160	1 to 160	15 to 2500
Dual	DP-350	1 to 350	1 to 350	15 to 5000
Dual	DP-600	1 to 600	1 to 600	15 to 9000
Dual	DP-700	1 to 700	1 to 700	15 to 10000

### STANDARD DELIVERY

- Basic Instrument
- Full set of Adaptors consisting of 1/8", 1/4", 3/8", 1/2" BSP (Set of NPT Adaptors available on request)
- Calibrated S.S Weight Sets - Refer Table ① & ②
- Spirit Level, Pointer Puller / Punch, Set of Spanners & Screw Driver
- Operating Fluid (500 ml)
- 'O' Ring & Seals
- Dust Cover, Wooden Carrying Case (for Weight Sets)
- Calibration Certificate from NABL Accredited Laboratory (as per ISO/IEC 17025:2005) - Refer Table ①
- Instruction Manual

### OPTIONALS

- Right angled Adaptor
- Two Gauge Adaptor
- Conversion Weight Sets to convert from one unit of Pressure to another
- Incremental Weight Sets for smaller increments of Pressure
- DWTCal Calibration Software
- Motorized Version